

MVC UNIVERSAL BATTERY CHARGERS

The most reliable manual controlled charger for battery formation, conditioning, testing and desulfation.



Features:

- Rugged Construction for maximum reliability in heavy duty industrial applications
- Wide Input Range available: Standard models cover European and North American AC Input values
- Wide Power Range available: Standard models from 1 to 36 kW, Output voltages up to 200 Vdc, Output current up to 200 Amp
- Charging curve IUa
- Intelligent electronic protection system (includes soft start, battery polarity reversal, output short circuit and overtemperature)
- Digital timer programmable up to 99h59m, with one-minute steps
- Charging curves available following user adjustment



Charlotte, NC

877.914.8999

info@GECIproducts.net

www.GECIproducts.net

TECHNICAL DATA					
MODEL NUMBER	OPPORTUNITY CHARGE	AC CURRENT DRAW 240V (A)	AC CURRENT DRAW 480V (A)	AC CURRENT DRAW 600V (A)	CABINET TYPE
IHF-MVC-64803-80/100	900/500	N/A	17.0	13.5	TL
IHF-MVC-42403-80/100	900/500	34.0	17.0	N/A	TL

*Other models available

*Specifications are subject to change

MODEL NUMBER BREAKDOWN

<u>IHF</u>	<u>MVC</u>	<u>64803</u>	<u>80</u>	<u>100</u>
↓	↓	↓	↓	↓
TECHNOLOGY (IGBT High Frequency)	CONTROL BOARD	INPUT VOLTAGE/PHASE 64803 (600/480/3PH) 42403 (480/240/3PH)	OUTPUT VOLTAGE	OUTPUT CURRENT

CABINET DIMENSIONS

(W x D x H in)

TL ▶ 21.97 x 23.86 x 21.61

WARRANTY

▶ 2 year full warranty